VISCOMETERS

RM 100 PLUS



Our most **modular viscometer**

The RM100 PLUS is the viscometer with largest speed and torque range available on market. Create your methods and store your results in relation with your application.

Temperature	Measu	are 🕇
	Viscosity : 225 mPa.s	Temperature : 22.4°C
USR USR	Torque : 5.116 mN.m	Measuring system MS-DIN 11
	Shear rate : 300 s ¹	Duration : 0 s

Programming and saving of methods.

PT 100 temperature probe included.

Wide torque and speed range.

Data memorization and transfer.

Available in standard and high sensitivity versions.





Viscometers







Rack stand in option

ECIEI

Type of instrument

Rotating springless viscometer with 7" Touch screen

Rotation speeds

Unlimited number of speeds between 0.3 and 1500 rpm

Torque range

Standard Version : 0.05 to 30 mNm LR Version : 0.005 to 0.8 mNm

Temperature

The RM 100 PLUS has a PT100 sensor which indicates temperatures between -50 °C to + 300 °C

Accuracy	Repea
+/-1 % of the full scale	+/- 0.29

atability

Display

Viscosity – Speed – Torque – Time – Temperature Choice of viscosity units: cP/Poises or mPa.s / Pa.s – Shear rate

Security and confidentiality

An «operator» function allows you to enter a username for you instrument. This user must then be identified using a 4-digit code. There is also a protected mode that locks your measurement

Language

French/English/Russian/Spanish

Compatible measuring system

MS DIN, MS ASTM, MS BV, MS VANE, MS R, MS HT, MS ULV, MS SV, MS CP

Compatible temperature control

EVA DIN, EVA MS-R, EVA LR-BV, RT1, RT3, CP1

Supply voltage	
90-240 VAC 50/60 Hz	

PC connections RS232 Port and USB **Printer connection** USB Host Port - Compatible PCL/5

Analog output 4 - 20 mA

Options

Carry case (PN 100500) Rack stand (PN P008000) Software (PN 311003)

Dimensions and weight

Head: L180 x W135 x H250 mm Hardened steel stand: L280 x W200 x H30 mm Stainless steel rod: Length 500 mm Weight: 6.7 kg

Available instruments :

Part Number Instrument	Designation Instrument
N100000	RM 100 PLUS VISCOMETER
N100115	RM 100 PLUS AC115 VISCOMETER
N100120	RM 100 PLUS VISCOMETER WITH MS-R 2-3-4 IN CASE
N100265	RM 100 PLUS AC 265 VISCOMETER
N100301	RM 100 PLUS LR VISCOMETER
N102000	RM 100 PLUS VISCOMETER WITH MS-R1 TO 5 IN CASE
N104000	RM 100 PLUS VISCOMETER without stand
N104800	RM 100 PLUS LR VISCOMETER without stand