

# METERING PUMPS

## AMS Series

Flow rate up to 60 L/hr, working pressure up to 25 bar

- Manual stroke length adjustment
- Manual or self venting
- High strength membrane -5- year warranty
- Horizontal mounting
- PVDF pump head



- AMS MF digital multi-function
- AMS PH built-in pH reading and adjustment
- AMS RH built-in ORP reading and adjustment

- AMS PLUS constant / constant 1-10 multiplier 1-10 divider 1-10 / 1-100 / 1-1000 mA current signal
- AMS CO PLUS constant with divider 1/10
- AMS CL PLUS constant with level control and divider 1/10

### PUMP HEADS



PVDF

PP

AISI316

PMMA

LPV

P

### SUPPLIED ACCESSORIES



Level Probe with foot filter

1/2" or 3/4" Injection valve

# METERING PUMPS



## K Series

Flow rate up to 18 L/hr, working pressure up to 20 bar

- Manual stroke length adjustment
- Manual or self venting
- High strength membrane -5- year warranty
- Horizontal mounting
- PVDF pump head



- KMS DC digital constant
- KMS MF digital multi-function
- KMS PH built-in pH reading and adjustment
- KMS RH built-in ORP reading and adjustment
- KMS EN weekly timer and solenoid valve control
- KMS CL built-in chlorine reading and control

- K PLUS constant / constant 1-10 multiplier 1-10 divider 1-10 / 1-100 / 1-1000 mA current signal
- K CO PLUS constant with divider 1/10
- K CL PLUS constant with level control and divider 1/10

### PUMP HEADS

### SUPPLIED ACCESSORIES



PVDF



PP



AISI316



PMMA



LPV



P



Level Probe with foot filter



1/2" Injection valve

# METERING PUMPS

## T Series

Flow rate up to 100 L/hr, working pressure up to 20 bar

- Electronic flow adjustment
- Manual or self venting
- High strength membrane - 5 - year warranty
- Wall mounting
- PVDF pump head



- TMS DC digital constant
- TMS MF digital multi-function
- TMS PH built-in pH reading and adjustment
- TMS RH built-in ORP reading and adjustment

- TCO constant
- TCL constant with level control

### PUMP HEADS



PVDF      PP      LPV      P

### SUPPLIED ACCESSORIES



Level Probe with foot filter      1/2" or 3/4" Injection valve

# METERING PUMPS



## V Series

Flow rate up to 16 L/hr, working pressure up to 20 bar

- Réglage électronique du débit
- Purge manuelle ou automatique
- Membrane haute résistance - garantie 5 ans
- Montage mural
- Tête de pompe en PVDF
- Modèles silencieux et ultra-silencieux également disponibles



- VMS MF digital multi-function
- VMS PO built-in pH or ORP reading and control (set by menu)
- VMS EN weekly timer and solenoid valve control

- VCO constant
- VCL constant with level control

### PUMP HEADS



PVDF  
Manual venting



PP  
Manual venting



PVDF  
Self venting



PP  
Self venting

### SUPPLIED ACCESSORIES



Level Probe  
with foot filter



1/2" Injection  
valve

# METERING PUMPS

## WDPHXX Series

Flow rate up to 10 L/hr, working pressure up to 7 bar

- Digital programmable controller with double metering pumps
- Wall mounting
- Easy control by ENCODER wheel with EASY-NAV rotation
- Double PVDF pump head
- RS485 output for remote control



WDPHRH acid (pH) and disinfectant (ORP)

WDPHCL acid (pH) and chlorine

WDPHCF acid, flocculant (gr/h) and 230 VAC output for chlorine

WDPHCA acid, anti-algae and 230 VAC output for chlorine

WDPHOS acid (pH) and active oxygen

### PUMP HEADS



PVDF

Manual venting



PP

Manual venting



PVDF

Self venting



PP

Self venting

### SUPPLIED ACCESSORIES



Level Probe  
with foot filter



Clapet d'injection  
1/2"